

API

A Domains

1. Check Availability

Checks availability of the specified domain name

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/checkDomain?APIKey=ZvSNmbNAKaL2Cah&websiteName=example.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
websiteName	Domain Name that you need to check the availability.	Required	String

Response:

responseMsg:

 statusCode: If 200 then domain is available and 400 not available.

 Message: Indicates the message

responseData:null

2 Register

Registers the domain name.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/Order?APIKey=ZvSNmbNAKaL2Cah&ProductType=1&Websitename=domainexample.com&Duration=1&IsWhoisProtection=true&ns1=nameserver1&ns2=nameserver2&ns3=nameserver3&ns4=nameserver4&Id=00&couponCode=couponcode>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
ProductType	Value:1 by Default	Required	Integer
Websitename	Domain Name that you need register.	Required	String
Duration	Number of years for which you wish to Register this domain name.	Required	Integer
IsWhoisProtection	Adds the Privacy Protection service for the domain name.	Required	boolean
ns1	The Name Servers 1 of the domain name.	Required	String
ns2	The Name Servers 2 of the domain name.	Required	String
ns3	The Name Servers 3 of the domain name.	Optional	String
ns4	The Name Servers 4 of the domain name.	Optional	String
Id	The Customer id for whom you wish to Register this domain name.	Required	Integer

Response:

responseMsg:

statusCode: If 200 then domain is register and other then 200 if domain is not register.

Message: Indicates the message and also reason if domain is not register.

responseData:

Null if domain is not register

creationDate: Indicates creation date of registered domain

expiryDate:Indicates expiry date of registered domain"

Msg:Indicates registry command message

msgCode :Indicates registry command code.

Name: Domain name registered.

3 Transfer

Transfer-in the domain name with us.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/TransferOrder?APIKey=ZvSNmbNAKaL2Cah&OrderType=4&Websitename=domainexample.com&IsWhoisProtection=true&AuthCode=authcode&Id=00>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
OrderType	Value:4 by Default	Required	Integer
Websitename	Domain Name that you need register.	Required	String
IsWhoisProtection	Adds the Privacy Protection service for the domain name.	Optional	boolean
Authcode	Epp Domain Secret	Required	String
Id	The Customer id for whom you wish to Register this domain name.	Required	Integer

Response:

responseMsg:

statusCode: 200 if domain is transfer and other then 200 if not transfer.

Message: Indicates the message and also reason if domain is not transfer.

responseData:

Null if domain is not Transfer

responseMsg:

statusCode: 200 if domain transfer process is completed and it waiting for approval for losing registrar and other then 200 if domain transfer is stall(locked or authcode invalid).

Message: Indicates the message and also reason for stall.

4 Cancel Transfer

Cancel the domain Transfer-In with us till the order is in stall status.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/CancelTransfer?APIKey=ZvSNmbNAKaL2Cah&id=00>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
id	Domain Id of the domain that you want to Cancel the Transfer	Required	Integer

Response:

responseMsg:

 statusCode: 200 if transfer cancel is successful and other then 200 if transfer cancel failed .

 Message: Indicates the message and also reason if domain is not cancel.

responseData:null

5 Validate a Transfer

Transfer a domain name with us.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/syncTransfer?APIKey=ZvSNmbNAKaL2Cah&domainName=domainexample.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainName	Domain for you want to validate the transfer	Required	Integer

Response:

responseMsg:

 statusCode: 200 if transfer for the domain was placed and 404 if transfer of domain was not placed

 Message: Indicates the message.

responseData:

Status: Indicates Transfer Order status.

Reason : Reason if order is cancel or stall

expiryDate: new expiry date of domain if order is completed

6 Renew

Transfer a domain name with us.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/RenewalOrder?APIKey=ZvSNmbNAKaL2Cah&OrderType=2&WebsiteName=domainexample.com&IsWhoisProtection=true&Duration=authcode&Id=00>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
OrderType	Represents the Order Type(2 for renewal)	Required	int
Duration	No of years	Required	int
	Domain name you want to renew	Required	String
Id	Represents customer Id	Required	int
IsWhoisProtection	Adds the Privacy Protection service for the domain name.	Optional	boolean

Response:

responseMsg:

statusCode: 200 if domain is renew and 404/400 if domain was not renew

Message: Indicates the message.

responseData:

statusCode: Registry Status code.

Message: Message and reason.

Exdate: new Expiry date

domainName: Domain Name of renewed domain.

7 Getting Details of the Domain using Id

Getting Registered Domain details with us by Id.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ViewDomainById?APIKey=ZvSNmbNAKaL2Cah&id=00>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
id	Id of the Domain whose details need to be fetched.	Required	int

Response:

responseMsg:

statusCode: 200 if domain is available in our records and 404 if not found

Message: Indicates the message.

responseData:

domainNameId: domainNameId

websiteName: domain name

orderDate: Order date and time of domain in timestamp in timestamp

creationDate: Registry Creation Date and time of domain in timestamp

lastUpdatedDate: Domain Modification Date and time of domain in timestamp

expirationDate: Registry Expiry Date and time of domain in timestamp

nameserver1: Nameservers 1

nameserver2: Nameservers 2

nameserver3: Nameservers 3

nameserver4: Nameservers 4

nameserver5: Nameservers 5

nameserver6: Nameservers 6

nameserver7: Nameservers 7

nameserver8: Nameservers 8

nameserver9: Nameservers 9

nameserver10: Nameservers 10

nameserver11: Nameservers 11

nameserver12: Nameservers 12

nameserver13: Nameservers 13

Status: Status under the System (currentstatus) - value will be *InActive*, *Active*, *Suspended*, *Pending Delete Restorable*, *Deleted*.

Authcode: Domain Secret key

isDomainLocked: Domain Lock Status

isThiefProtected Thief Protection Status

isPrivacyProtection: Privacy Protection Status
isParked: domain Parked Status
customerId: Customer Id to which domain Belongs
registrantContactId : Registrant Contact
adminContactId: Admin Contact
technicalContactId: TechnicalContact
billingContactId: Billing Contact
isRegistrantVerification: RAA Verification Status
registrantVerificationDate:RAA verification Date
websiteId: website Id for reference
dnszoneStatus: dns is active or not
dnszoneId: dns id

8 Getting Details of the Domain using Domain Name

Getting Registered Domain details with us by Domain Name.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ViewDomain?APIKey=ZvSNmbNAKaL2Cah&websiteName=example.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
websiteName	name of the Domain whose details need to be fetched.	Required	String

Response:

responseMsg:

statusCode: 200 if domain is available in our records and 404 if not found

Message: Indicates the message.

responseData:

domainNameId: domainNameId

websiteName: domain name

orderDate: Order date and time of domain in timestamp in timestamp

creationDate: Registry Creation Date and time of domain in timestamp

lastUpdatedDate: Domain Modification Date and time of domain in timestamp

expirationDate: Registry Expiry Date and time of domain in timestamp

nameserver1: Nameservers 1

nameserver2: Nameservers 2

nameserver3: Nameservers 3

nameserver4: Nameservers 4

nameserver5: Nameservers 5

nameserver6: Nameservers 6

nameserver7: Nameservers 7

nameserver8: Nameservers 8

nameserver9: Nameservers 9

nameserver10: Nameservers 10

nameserver11: Nameservers 11

nameserver12: Nameservers 12

nameserver13: Nameservers 13

Status: Status under the System (currentstatus) - value will be *InActive*, *Active*, *Suspended*, *Pending Delete Restorable*, *Deleted*.

Authcode: Domain Secret key

isDomainLocked: Domain Lock Status
 isThiefProtected Thief Protection Status
 isPrivacyProtection: Privacy Protection Status
 isParked: domain Parked Status
 customerId: Customer Id to which domain Belongs
 registrantContactId : Registrant Contact
 adminContactId: Admin Contact
 technicalContactId: TechnicalContact
 billingContactId: Billing Contact
 isRegistrantVerification: RAA Verification Status
 registrantVerificationDate:RAA verification Date
 websiteId: website Id for reference
 dnszoneStatus: dns is active or not
 dnszoneId: dns id

9 Search

Getting Registered Domain details with us by Domain Name.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/SearchDomainList?APIKey=ZvSNmbNAKaL2Cah&page=1&maxIndex=10&searchQuery=test>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
page	Page for which details needs to be fetched	Required	int
maxIndex	Max no of records needs to be fetch	Required	int
searchQuery	Filter	Optional	string

Response:

totalCount: Total No of domain Count.

record:

Array of domain with following details:

entryId: Domain Id.

domainName: example.com

expirationDate: registry expiry date.

creationDate: registry creation date.

actionStatus: Domain status in system.

resellerId: Reseller Id under which domain is register.

customerId: Customer Id under which domain is register,

10 Modify Nameserver of Domain.

To update Domain Name Server in Registry

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/UpdateNameServer?APIKey=ZvSNmbNAKaL2Cah&domainNameId=1&websiteName=domainexample.com&nameServer1=nameServer1&nameServer2=nameServer2&nameServer3=nameServer3&nameServer4=nameserver4&Id=00>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain name Id	Required	Integer
WebsiteName	Domain Name.	Required	String
nameServer1	New Name Servers 1 of the domain name.	Optional	String

nameServer2	New Name Servers 2 of the domain name.	Optional	String
nameServer3	New Name Servers 3 of the domain name.	Optional	String
nameServer4	New Name Servers 4 of the domain name.	Optional	String
nameServer5	New Name Servers 5 of the domain name.	Optional	String
nameServer6	New Name Servers 6 of the domain name.	Optional	String
nameServer7	New Name Servers 7 of the domain name.	Optional	String
nameServer8	New Name Servers 8 of the domain name.	Optional	String
nameServer9	New Name Servers 9 of the domain name.	Optional	String
nameServer10	New Name Servers 10 of the domain name.	Optional	String
nameServer11	New Name Servers 11 of the domain name.	Optional	String
nameServer12	New Name Servers 12 of the domain name.	Optional	String
nameServer13	New Name Servers 13 of the domain name.	Optional	String

Response:

responseMsg:

statusCode: If 200 nameserver is modify and other then 200 if nameserver modification failed.

Message: Indicates the message and also reason if domain is not register.

responseData:

msg:Message from registry

msgCode: Message code from registry

11 Manage Lock on Domain

Registers a domain name.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDomainLock?APIKey=>

ZvSNmbNAKaL2Cah&domainNameId=1&websiteName=domainexample.com&isDomainLocked=true

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain name Id	Required	Integer
websiteName	Domain Name.	Required	String
isDomainLocked	Lock Status for domain.	Required	Boolean

Response:

responseMsg:

statusCode: 200 if manage lock action is successful and other then 200 if manage lock action failed.

Message: Indicates the message:

responseMsg:

statusCode: 200 if manage lock action is successful and other then 200 if manage lock action failed.

Message: Indicates the message:

11 Manage Privacy on Domain

To allow Reseller to manage domain privacy protection.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDomainPrivacyProtection?APIKey=ZvSNmbNAKaL2Cah&domainNameId=1&iswhoisprotected=true>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain name Id	Required	Integer
iswhoisprotected	Privacy Status for domain.	Required	Boolean

Response:

responseMsg:

statusCode: 200 if Manage Privacy action is successful and other then 200 if manage Privacy action failed.

Message: Indicates the message

responseData:

responseMsg:

statusCode: 200 if Manage Privacy action is successful and other then 200 if manage Privacy action failed.

Message: Indicates the message

12 Manage Domain Suspend

To allow Resellers to manage domain suspend action.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDomainSuspend?APIKey=ZvSNmbNAKaL2Cah&domainNameId=1&websiteName=domainexample.com&isDomainSuspend=true>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain name Id	Required	Integer
websitename	Domain Name.	Required	String
isDomainSuspend	Privacy Status for domain.	Required	Boolean

Response:

responseMsg:

statusCode: If 200 domain suspend action is successful and 400 if domain suspend action failed.

Message: Indicates the message.

responseData:

responseMsg:

statusCode: If 200 nameserver suspend action successful and 400 if nameserver suspend action failed.

Message: Indicates the message.

Modification.

13 Manage Theft Protection on Domain

To allow Reseller to manage domain privacy protection.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ManageTheftProtection?APIK>

ey=ZvSNmbNAKaL2Cah&domainNameId=1&websiteName=domainexample.com&isTheftProtection=true

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain name Id	Required	Integer
websiteName	Domain Name.	Required	String
isTheftProtection	Privacy Status for domain.	Required	Boolean

Response:

responseMsg:

statusCode: 200 if theft protection action on domain is successful and 400 if theft protection action on domain is failed.

Message: Indicates the message.

responseData:

responseMsg:

statusCode: 200 if theft protection action on domain is successful and 400 if theft protection action on domain is failed.

Message: Indicates the message and also reason if domain is not register.

14 View Domain Secret Key

View Domain EPP secret key

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ViewEPPCode?APIKey=ZvSNmbNAKaL2Cah&domainNameId=id>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Id of the Domain whose epp code to be fetched.	Required	int

Response:

DomainScretkey

15 Manage DNS Management

To Active DNS for Domain.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ManageDNSRecords?APIKey=ZvSNmbNAKaL2Cah&WebsiteId=i>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
WebsiteId	Refer website Id which we get in view domain response	Required	int

Response:

responseMsg:

statusCode: 200 if dns management action on domain is successful and 400 if dns management action on domain is failed.

Message: Indicates the message.

responseData:

responseMsg:

statusCode: 200 if dns management on domain is successful and 400 if theft dns management on domain is failed.

Message: Indicates the message and also reason if domain is not register.

16 Add DNS Record

To add DNS record for Domain.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/AddDNSRecord?APIKey=ZvSNmbNAKaL2Cah&DNSZoneID=00'&RecordName=host.example.com'&RecordType=A&RecordValue=recordvalue&RecordPriority=0&RecordTTL=43200>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
DNZZoneID	Dnszone id which we get in view domain response	Required	int
RecordName	Name for dns entry	Required	String
RecordType	Type for dns entry	Required	String
RecordValue	Value for dns entry	Optional	int
RecordTTL	Time to live	Optional	int
RecordPriority	Set priority	Optional	int

Response:

responseMsg:

statusCode: 200 if dns record is added successfully domain is successful and 400 if dns record is add on domain is failed.

Message: Indicates the message.

responseData:

responseMsg:

statusCode: 200 if dns record is added successfully domain is successful and 400 if dns record is add on domain is failed.

Message: Indicates the message.

17 Modify DNS Record

To Modify DNS record for Domain.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyDNSRecord?APIKey=ZvSNmbNAKaL2Cah&DNSZoneID=00&DNSZoneRecordID=00&RecordName=host.example.com'&RecordType=A&RecordValue=recordvalue&RecordTTL=43200>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
DNZZoneID	Dnszone id which we get in view domain response	Required	int
DNZZoneRecordID	Dnszone record iD for which we want to modify the domain		
RecordName	Name for dns entry	Required	String
RecordType	Type for dns entry	Required	String
RecordValue	Value for dns entry	Optional	int
RecordTTL	Time to live	Optional	int

Response:

responseMsg:

statusCode: 200 if dns record is modify successfully and 400 if dns record modification is failed.

Message: Indicates the message.

responseData:

statusCode: 200 if dns record is added successfully and 400 if dns record modification is failed.

Message: Indicates the message.

18 Delete DNS Record

To delete DNS record for Domain.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/DeleteDNSRecord?APIKey=ZvSNmbNAKaL2Cah&DNSZoneID=00&DNSZoneRecordID=00>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
DNSZoneID	Dnszone id which we get in view domain response	Required	int
DNSZoneRecordID	Dnszone record iD for which we want to modify the domain	Required	int

Response:

responseMsg:

statusCode: 200 if delete dns record is deleted successfully and 400 if delete dns record is failed.

Message: Indicates the message.

responseData:

statusCode: 200 if dns record is deleted successfully and 400 if delete dns record is failed.

Message: Indicates the message.

19 View DNS Records

To view all DNS records.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ViewDNSRecord?APIKey=ZvSNmbNAKaL2Cah&WebsiteId=id>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
WebsiteId	Refer website Id which we get in view domain response	Required	int

Response:

responseMsg:

statusCode: 200 if dns record list is fetch successfully and 400 if dns record list is fetch failed.

Message: Indicates the message.

responseData:

responseMsg:

statusCode: 200 if dns management on domain is failed and 400 if theft dns management on domain is failed.

Message: Indicates the message and also reason if domain is not register.

19 Modifying Domain Contact

Modifies contacts of the specified register Domain

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/updatecontact?APIKey=ZvSNmbNAKaL2Cah&domainNameId=1&websiteName=domainexample.com&adminContactId=1234&billingContactId=4567®istrantContactId=7891&technicalContactId=1235>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String

domainNameId	Domain name Id	Required	Integer
Websitename	Domain Name.	Required	String
adminContactId	The Contact Id that you want to use as the new Admin Contact.	Required	String
billingContactId	The Contact Id that you want to use as the new Billing Contact.	Required	String
registrantContactId	The Contact Id that you want to use as the new Registrant Contact.	Required	String
technicalContactId	The Contact Id that you want to use as the new Technical Contact.	Required	String

Response:

responseMsg:

statusCode: 200 if Domain Contact Updated Successfully and 400 Domain Contact Updation is failed.

Message: Indicates the message.

responseData:

responseMsg:

statusCode: 200 if Domain Contact Updated Successfully and 400 Domain Contact Updation is failed.

Message: Indicates the message and also reason if domain is not register.

20 To move domain from one client to another

To move registered domain from one reseller to another

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/movedomain?APIKey=ZvSNm>

bNAKaL2Cah&domainNameId=1&customerId=123&userName=abc@example.com&isCustomerContact=1

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain name Id which need to be move	Required	Integer
customerId	Client Id in domain needs to be moved.	Required	Integer
userName	UserName of client in which domain needs to be moved .	Required	String
isCustomerContact	1 indicates if we want to use default contact of new client. 0 if we want to use existing Contact		

Response:

responseMsg:

statusCode: 200 if domain is moved successfully and 400 if domain move is failed.

Message: Indicates the message.

responseData:

responseMsg:

statusCode: 200 if domain is moved successfully and 400 if domain move is failed.

Message: Indicates the message and also reason if domain is not register.

21. Check Availability

Checks availability of the specified domain name and bases on domainType show their pricing

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/checkdomainavailable?APIKey=ZvSNmbNAKaL2Cah&websiteName=example.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
websiteName	Domain Name that you need to check the availability.	Required	String

Response:

responseMsg:

statusCode: If 200 then show domain pricing and 400 not available.

Message: Indicates the message

responseData:

domainType:Indicate domain type

Available:check domain is available or not

registrationFees:Indicate registration fee

renewalfees:Indicate renewal fee

transferFees:Indicate transfer fee

22. Show Pricing

Checks availability of the specified domain name

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/getdomainprice?APIKey=ZvSNmbNAKaL2Cah&websiteName=example.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
websiteName	Domain Name that you need to check the availability.	Required	String

Response:

responseMsg:

statusCode: If 200 then domain is available and 400 not available.

Message: Indicates the message

responseData:

registrationFees:Indicate registration fee

renewalfees:Indicate renewal fee

transferFees:Indicate transfer fee

B Contact

1 Add Contact

To add the Contact under Customer

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/AddRegistrantContact?APIKey=ZvSNmbNAKaL2Cah&Name=johndeo&EmailAdress=johndeo@example.com&CompanyName=example&Address=exampleaddress&City=examplecity&StateName=examplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate_Phone_cc=00&Alternate_Phone=&Id=00

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
Name	Name of the Contact	Required	String
EmailAdress	Email address of the Contact	Required	String
CompanyName	Compnay name of the Contact	Required	String
Address	Address of the Contact	Required	String
City	City of the Contact	Required	String
StateName	State of the Contact	Required	String
CountryName	Country of the Contact	Required	String
Zip	Zip code of the Contact	Required	String
PhoneNo_cc	Phone no Country Code of the Contact	Required	String
PhoneNo	Phone no of the Contact	Required	String
Faxno_cc	Fax no country code of the Contact	Optional	String

FaxNo	Fax no of the Contact	Optional	String
Alternate_Phone_cc	Alternate phone no country code of the Contact	Optional	String
Alternate_Phone	Alternate phone no of the Contact	Optional	String
Id	Client id for which you want modify the details of RegistrantContact	Required	int

Response:

responseMsg:

statusCode: 200 if Contact is modify successfully and 400 if modifying Contacts failed.

Message: Indicates the message.

responseData:

statusCode: 200 if Contact is modify successfully and 400 if modifying Contacts failed.

Message: Indicates the message.

2 Modify Contact

To Modify the Contact

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyRegistrantContact?APIKey=ZvSNmbNAKaL2Cah&Name=johndeo&EmailAddress=johndeo@example.com&CompanyName=example&Address=exampleadress&City=examplecity&StateName=exa>

[mplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate_Phone_cc=00&Alternate_Phone=&RegistrantContactId=00](#)

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
Name	Name of the Contact	Required	String
EmailAdress	Email address of the Contact	Required	String
CompanyName	Compnay name of the Contact	Required	String
Address	Address of the Contact	Required	String
City	City of the Contact	Required	String
StateName	State of the Contact	Required	String
CountryName	Country of the Contact	Required	String
Zip	Zip code of the Contact	Required	String
PhoneNo_cc	Phone no Country Code of the Contact	Required	String
PhoneNo	Phone no of the Contact	Required	String
Faxno_cc	Fax no country code of the Contact	Optional	String
FaxNo	Fax no of the Contact	Optional	String
Alternate_Phone_cc	Alternate phone no country code of the Contact	Optional	String
Alternate_Phone	Alternate phone no of the Contact	Optional	String
RegistrantContactId	Customer If for which you want add contact	Required	int

Response:

responseMsg:

statusCode: 200 if Contact is added successfully and 400 if adding Contacts failed.

Message: Indicates the message.

responseData:

statusCode: 200 if Contact is added successfully and 400 if adding Contacts failed.

Message: Indicates the message.

3 View Contact

To View the Contact details

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ViewRegistrant?APIKey=ZvSNmbNAKaL2Cah&RegistrantContactId=00>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
RegistrantContactId	RegistrantContactId for which you want view contact	Required	int

Response:

responseMsg:

statusCode: 200 if Contact is available and 404 if Contact is not available.

Message: Indicates the message.

responseData:

Name: Name of the Contact.

EmailAddress: Email address of the Contact.

CompanyName: CompanyName of the Contact.

Address:Email address of the Contact.

City:City of the Contact.

StateName: State of the Contact.

CountryName: Country of the Contact.

Zip: Zip code of the Contact.

PhoneNo_cc: Phone no country code of the Contact.

PhoneNo: Phone no address of the Contact.

Faxno_cc: Fax no country code of the Contact.

FaxNo: Fax no of the Contact.

Alternate_Phone_cc: Alternate Phone no of the Contact.

Alternate_Phone: Alternate Phone no of the Contact

clientId: Customer Id to which Contact belongs.

C Client

1 Add Client

To add the new Customer

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/AddClient?APIKey=ZvSNmbNAKaL2Cah&FirstName=johndeo&UserName=johndeo@example.com&Password=password&CompanyName=example&Address1=exampleadress&City=examplecity&StateName=examplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate_Phone_cc=00&Alternate_Phone=

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
Name	Name of the Client	Required	String
UserName	Email address of the Client	Required	String
Password	Password of the Client		
CompanyName	Company name of the Client	Required	String
Address1	Address of the Client	Required	String
City	City of the Client	Required	String
StateName	State of the Client	Required	String
CountryName	Country of the Client	Required	String
Zip	Zip code of the Client	Required	String
PhoneNo_cc	Phone no Country Code of the Client	Required	String
PhoneNo	Phone no of the Client	Required	String
Faxno_cc	Fax no country code of the Client	Optional	String
FaxNo	Fax no of the Client	Optional	String

Alternate_Phone_cc	Alternate phone no country code of the Client	Optional	String
Alternate_Phone	Alternate phone no of the Client	Optional	String

Response:

responseMsg:

statusCode: 200 if client is add successfully and 400 if adding client failed.

Message: Indicates the message.

responseData:

statusCode: 200 if client is add successfully and 400 if adding client failed.

Message: Indicates the message.

2 Modify Client

To modify client

Method: GET

URL:

https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyClient?APIKey=ZvSNmbNAKaL2Cah&FirstName=johndeo&UserName=johndeo@example.com&Password=password&CompanyName=example&Address=exampleaddress&City=examplecity&StateName=examplestate&CountryName=CountryName&Zip=000&PhoneNo_cc=00&PhoneNo=0000000000&Faxno_cc=00&FaxNo=00&Alternate_Phone_cc=00&Alternate_Phone=&Id=00

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
Id	Customer Id for which you want to modify the details	Required	int
FirstName	Name of the Client	Optional	String
UserName	Email address of the Client	Optional	String
Password	Password of the Client	Optional	
CompanyName	Company name of the Client	Optional	String
Address1	Address of the Client	Optional	String
Address1	Address of the Client	Optional	String
City	City of the Client	Optional	String
StateName	State of the Client	Optional	String
CountryName	Country of the Client	Optional	String
Zip	Zip code of the Client	Optional	String
PhoneNo_cc	Phone no Country Code of the Client	Optional	String
PhoneNo	Phone no of the Client	Optional	String
Faxno_cc	Fax no country code of the Client	Optional	String
FaxNo	Fax no of the Client	Optional	String
Alternate_Phone_cc	Alternate phone no country code of the Client	Optional	String
Alternate_Phone	Alternate phone no of the Client	Optional	String

Response:

responseMsg:

statusCode: 200 if client is add successfully and 400 if adding client failed.

Message: Indicates the message.

responseData:

statusCode: 200 if client is add successfully and 400 if adding client failed.

Message: Indicates the message.

3 View Client

To View the Client details

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ViewClient?APIKey=ZvSNmbNAKaL2Cah&UserName=username@example.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
UserName	UserName for which you want view client details	Required	String

Response:

responseMsg:

statusCode: 200 if Contact is available and 404 if Contact is not available.

Message: Indicates the message.

responseData:

clientId: Id of Client

resellerId: reseller Id to which Client belongs.

firstName: Name of the Client.

companyName: Email address of the Client.
userName: userName/email address of the Client.
password: password of the Client.
address: address of the Client.
city:City of the Client.
state: State of the Client.
country: Country of the Client.
zip: Zip code of the Client.
phoneNo_cc: Phone no country code of the Client.
phoneNo: Phone no address of the Client.
faxno_cc: Fax no country code of the Client.
faxNo: Fax no of the Client.
alternate_Phone_cc: Alternate Phone no of the Client.
alternate_Phone: Alternate Phone no of the Client.

4 Change the Client Password

To modify client's password

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ChangeClientPassword?APIKey=ZvSNmbNAKaL2Cah&UserName=johndeo@example.com&OldPassword=password&NewPassword=example>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String

UserName	Email address of the Client	Required	String
OldPassword	Existing Password of the Client		
Password	New Password of The Client	Required	String

Response:

responseMsg:

statusCode: 200 if client is password is change successfully and 400 if client password change failed.

Message: Indicates the message.

responseData:

statusCode: 200 if client is password is change successfully and 400 if client password change failed.

Message: Indicates the message.

5 To Delete the Client

To delete the client

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/DeleteCustomer?APIKey=ZvSNmbNAKaL2Cah&customerId=0000>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
customerId	Client Id which you want to delete	Required	Int

Response:

responseMsg:

statusCode: 200 if client is delete successfully and 400 if client delete failed.

Message: Indicates the message.

responseData:

200 if client is delete successfully and 400 if client delete failed.

Message: Indicates the message.

E Host

1 To Add Child Name Servers

To add child name server

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/AddChildNameServer?APIKey=ZvSNmbNAKaL2Cah&domainNameId=domainId&websiteName=example.com&ipAddress=127.0.0.1&hostName=example>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to add child name server	Required	int
websiteName	Domain name of registered domain for which you want to add child name server	Required	String
hostName	Child Name server which you want to add	Required	String
ipAddress	Ip address which you want associate with the Child Name Servers	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is modaddified successfully and 400 if child name server add failed.

Message: Indicates the message.

responseData:

statusCode: 200 if child name server is add successfully and 400 if child name server add failed.

Message: Indicates the message.

2 Modify Name Servers IP

To modify Ip address of child name server

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyChildNameServerIP?APIKey=ZvSNmbNAKaL2Cah&domainNameId=domainId&websiteName=example.com&oldIpAddress=127.0.0.1&newIpAddress=127.0.0.2&hostName=example>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to modify child name server	Required	int
websiteName	Domain name of registered domain for which you want to modify child name server	Required	String
hostName	Child Name server which you want to modify	Required	String
newIpAddress	New Ip address which you want associate with the Child Name Servers	Required	String
oldIpAddress	old Ip address	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is added successfully and 400 if child name server add failed.

Message: Indicates the message.

responseData:

statusCode: 200 if child name server is added successfully and 400 if child name server add failed.

Message: Indicates the message.

3 To Modify Host Child Name Servers

To modify Child Name Server of Domain

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/ModifyChildNameServerHost?APIKey=ZvSNmbNAKaL2Cah&domainNameId=domainId&websiteName=example.com&oldHostName=example&newHostName=example>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to modify child name server	Required	int
websiteName	Domain name of registered domain for which you want to modify child name server	Required	String
oldHostName	Old Child Name server which you want to modify	Required	String
newHostName	New Child Name Server which you want modify	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is modify successfully and 400 if child name server modify failed.

Message: Indicates the message.

responseData:

statusCode: 200 if child name server is modify successfully and 400 if child

name server modify failed.

Message: Indicates the message.

4 To Delete Child Name Servers

To delete Child Name Server

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/DeleteChildNameServer?APIKey=ZvSNmbNAKaL2Cah&domainNameId=domainId&websiteName=example.com&ipAddress=127.0.0.1&hostName=example>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to delete child name server	Required	int
websiteName	Domain name of registered domain for which you want to delete child name server	Required	String
hostName	Child Name server which you want to delete	Required	String

Response:

responseMsg:

statusCode: 200 if child name server is delete successfully and 400 if child name server delete failed.

Message: Indicates the message.

responseData:

statusCode: 200 if child name server is delete successfully and 400 if child name server delete failed.

Message: Indicates the message.

5 To Get Child Name Servers of a Domain

To get child name servers of a mention domain Id

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/getchildnameservers?APIKey=ZvSNmbNAKaL2Cah&id=domainId>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
Id	Domain id of registered domain for which you want to get child name server list	Required	int

Response:

responseMsg:

statusCode: 200 if child name servers list are is fetch successfully and 400 if child name servers list fetch failed.

Message: Indicates the message.

responseData:

[

```

    {"hostname": "ns1.example.com", "ipAddress": "127.0.0.1"},
    {"hostname": "ns2.example.com", "ipAddress": "127.0.0.1"},
    {"hostname": "ns3.example.com", "ipAddress": "127.0.0.1"},
    {"hostname": "ns4.example.com", "ipAddress": "127.0.0.1"}
  ]

```

F Domain Forwarding

1 To set Domain Forwarding

To set domain forwarding for the domain registered with us.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/SetDomainForwarding?APIKey=ZvSNmbNAKaL2Cah&domainNameId=domainId&websiteId=websiteId&isMasking=1&rewrite=http://www.exampleple.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to set Domain Forwarding	Required	int
websiteId	DomainWebsite id of registered domain for which you want to set Domain Forwarding(Refer website Id from view domain response).	Required	String
isMasking	Possible value is 1 or 0. If 1 , visitors will see the source URL and not the destination URL	Required	int
rewrite	URL where you want to forward your domain	Required	String

Response:

responseMsg:

statusCode: 200 if domain forwarding details are added successfully and 400 if domain forwarding details addition failed.

Message: Indicates the message.

responseData:

statusCode: 200 if domain forwarding details are added successfully and 400 if domain forwarding details addition failed.

Message: Indicates the message.

2 To get Domain Forwarding details

To get domain forwarding details of mention website

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/GetDomainForwarding?APIKey=ZvSNmbNAKaL2Cah&websiteId=websiteId>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
websiteId	Domain Website id of registered domain for which you want to get Domain Forwarding details.(Refer website Id from view domain response)	Required	int

Response:

responseMsg:

statusCode: 200 if domain forwarding details are fetch successfully and 400 if domain forwarding details fetch failed.

Message: Indicates the message.

responseData:

```
{  
  "websiteName": "example.com",  
  "resellerId": id,  
  "isMasking": 1,  
  "rewrite": redirect URL if masking is disable or null,  
  "proxyPass": redirect URL if masking is enable or null,  
}
```

3 To Update Domain Forwarding details

To update domain forwarding details of the domain.

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/updatedomainforwarding?APIKey=ZvSNmbNAKaL2Cah&domainNameId=domainId&websiteId=websiteId&isMasking=1&rewrite=http://www.exampleple.com>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
------------	-------------	---------------------	------

APIKey	Authentication Parameters	Required	String
domainNameId	Domain id of registered domain for which you want to update Domain Forwarding	Required	int
websiteId	DomainWebsite id of registered domain for which you want to update Domain Forwarding.(Refer website Id from view domain response)	Required	String
isMasking	Possible value is 1 or 0. If 1 , visitors will see the source URL and not the destination URL	Required	int
rewrite	URL where you want to forward your domain	Required	String

Response:

responseMsg:

statusCode: 200 if domain forwarding details are updated successfully and 400 if domain forwarding updated failed.

Message: Indicates the message.

responseData:

statusCode: 200 if domain forwarding details are updated successfully and 400 if domain forwarding updated failed.

Message: Indicates the message.

4 To delete Domain Forwarding details

To delete Child Name Server

Method: GET

URL:

<https://api.connectreseller.com/ConnectReseller/ESHOP/deletedomainforwarding?APIKey=ZvSNmbNAKaL2Cah&websiteId=websiteId>

Request Parameters

Following table describes the request parameters of the pause object:

Parameters	Description	Required / Optional	Type
APIKey	Authentication Parameters	Required	String
websiteId	Domain Website id of registered domain for which you want to delete Domain Forwarding details.(Refer website Id from view domain response)	Required	int

Response:

responseMsg:

statusCode: 200 if domain forwarding details are deleted successfully and 400 if domain forwarding delete failed.

Message: Indicates the message.

responseData:

statusCode: 200 if domain forwarding details are deleted successfully and 400 if domain forwarding delete failed.

Message: Indicates the message.